

Oli lubrificanti

Lubricating oils



Lubricating oils are able to satisfy all vacuum pumps lubrication needs. Oils for pumps have a new formula based on highly selected substances of "Group II " and further additions fit to reach highest performances.

- Oils for pumps have high viscosity rate able to reduce oil viscosity changes within temperature variations therefore assuring a good lubrication also when applied to high service temperatures.*
- Oils for pumps are highly resistant against oxidation and ageing and could last longer preventing moistures or lime. Infact TOST (turbine oil stability test) has certified over 4000 hours lasting, widely covering oxidation rates foreseen by end users in IP 280 (CIGRE) test.*

- Thanks to their resistance to corrosion and rust, oils for pumps properly protect and preserve all lubricated components.*
- Oils for pumps have anti-foam properties and are able to disclose air thus preventing partial lubrication failure, cavitation issues, irregularities and pumps oil leakages.*
- Oils for pumps have best demulsify properties, they do not emulsify thus granting a quicker water separation, smooth and stable lubrication reducing friction and wear.*

GEV OIL

TYPE G 880

Viscosità a 40°C	Viscosity at 40°C	mm ² /s	64
Viscosità a 100°C	Viscosity at 100°C	mm ² /s	8,93
Indice di viscosità	Viscosity rate	-	114
Punto di infiammabilità V.A.	V.A. inflammability rate	°C	240
Punto di scorrimento	Lubrication temperature	°C	-15
Massa volumica a 15°C	Volumetric rate at 15°C	kg/l	0,86